Portable Gates











- > Moveable access control & security
- > Protect property & merchandise
- > High visibility of secured spaces
- > Limit access to machinery & hazardous areas
- Use in a variety of locations and applications
- > Custom powder coat colors available
- > 100% made in America



Access Control Gates

Product Code	In-Use Width	In-Use Height	Stacked Height	Stacked Width	Weight (LBS)
XL1265	up to 12'	6′	6' 6"	27"	122
XL665	adds up to 6'	6′	6' 6"	11"	59
XL1275	up to 12'	7′	7′ 6″	27"	146
XL675	adds up to 6'	7′	7′ 6″	11"	70

Barrier Gates

Product Code	In-Use Width	In-Use Height	Stacked Height	Stacked Width	Weight (LBS)
XL1240	up to 12'	41"	47"	27"	53
XL640	adds up to 6'	41"	47"	11"	24

SPECIFICATIONS

Finish: Galvanized, Powder Coat Colors Available

Webbing: $^3/_8" \times ^3/_4"$ 14-gauge Steel **Frame:** $1^{1}/_2" \times 1^{1}/_2"$ 12-gauge Angle Iron **Locking Bar:** $1^{1}/_2" \times 1^{1}/_2"$ 12-gauge Angle Iron

Hasp: 3/16" Steel Welded to Frame (padlock not included)

Support Bars: ³/₄" Round Steel Tubing Axle: 24" Wide with 11-gauge Steel Caster: 3" Locking Rubber Casters

Rivets: 3/16" x 1/2" Steel

Add-On Gates: Use for each additional 6' needed.

SPECIFICATIONS

Finish: Galvanized, Yellow and Black Powder Coat

Webbing: $^3/^8$ " x $^3/^4$ " 14-gauge Steel **Frame:** $1^{11}/^2$ " x $1^{11}/^2$ " 12-gauge Angle Iron **Locking Bar:** $1^{11}/^2$ " x $1^{11}/^2$ " 12-gauge Angle Iron

Hasp: 3/16" Steel Welded to Frame*

Axle: 14" Wide 11-gauge Steel, 3 Axles per Gate

Caster: 3" Locking Rubber Casters

Rivets: 3/16" x 1/2" Steel

Straps: 10" Long x 11/2" Wide, 14-gauge CRS **Add-On Gates:** Use for each additional 6' needed.

ECO[™] Gates

Product Code	In-Use Width	In-Use Height	Stacked Height	Stacked Width	Weight (LBS)
XLECO1265	up to 12'	6′	6′ 6″	27"	90
XLECO665	adds up to 6'	6′	6′ 6″	11"	45

Aisle Gates

Product	In-Use	In-Use	Stacked	Stacked	Weight
Code	Width	Height	Height	Width	(LBS)
AISLE GATE	7'	40"	40"	7"	12

SPECIFICATIONS

Finish: Galvanized Webbing, Gray Powder Coated Frame

Webbing: $^{3}/_{8}'' \times ^{3}/_{4}''$ 16-gauge Steel **Frame:** $1^{1}/_{2}'' \times 1^{1}/_{2}''$ 13-gauge Angle Iron **Locking Bar:** $1^{1}/_{2}'' \times 1^{1}/_{2}''$ 13-gauge Angle Iron

Hasp: 3/16" Steel Welded to Frame* **Caster:** $2^{1}/2"$ Rubber Casters

Rivets: 3/16" x 1/2" Steel

SPECIFICATIONS

Finish: Galvanized, Safety Yellow Powder Coated

Webbing: $\frac{3}{8}$ " x $\frac{3}{4}$ " 14-gauge Steel Frame: $1\frac{1}{2}$ " x $1\frac{1}{2}$ " 12-gauge Angle Iron

Handle/L-pin: 5/8" Steel (use as a handle or for ganging)

Feet: 14" Wide, 11-gauge Steel

Rivets: $\frac{3}{16}$ " x $\frac{1}{2}$ " Steel

Gate Accessories

Padlock: 2" Hardened Steel with Plated Shackle 8' Post: Lock Gate to Posts Instead of Wall or Casing

*Padlock not included, Cylinder Lock optional



SECURE Product
SECURE Areas
SECURE Access

